

Warranty

The model Guest Module 1 is covered by a 2 year warranty to be free from defective workmanship and materials. In the event that the Guest Module 1 needs repair, you must call us to get an authorization, and then carefully pack and ship it to us. You will pay for shipping to us and we will pay for return back to you, UPS ground. No free repairs will be made if the defect was caused by misuse, weather conditions, or other cause, except for defective workmanship or materials. THERE ARE NO EXPRESSED OR IMPLIED WARRANTIES WHICH EXTEND BEYOND THE WARRANTY HERE MADE.

Guest Module 1 Remote Keypad



User Guide

06/06

JK Audio, Inc. 1311 E 6th Street, Sandwich, IL 60548
USA

Voice: (815) 786-2929 Toll Free: 800-JK-Audio

Fax: 815-786-8502

Info@jkaudio.com www.jkaudio.com

JK Audio

Description

Guest Module 1 gives you remote access to the on-hook / off-hook and dial features of the Inn-keeper 1, 1r, 1x,1rx or Broadcast Host digital hybrids.

DTMF keypad
Keypad disable switch
Talk / Dial Button
Hang up Button
Ring / Call LED

Connection

Connect Guest Module 1 to your JK Audio digital hybrid using an 8 pin RJ45 modular cable. This cable provides remote power so there is no need for batteries or an external power pack. We have provided a 25 foot cable to cover most installations. If you need a custom length cable, be sure to purchase a cable wired so that the wire on pin 1 of each connector is the same color (pin 1 = pin 1). Data cables are usually wired pin 1 to pin 1, but telephone cables are usually wired pin 1 to pin 8.

Operating

The Call button will flicker when a call comes in. Press this button to answer or place a call. The button will stay lit when a call is present. When you dial on-air, the tones go out on the line, and do not come back mixed with the dial tone or caller signal. Guest Module 1 was designed exclusively for JK Audio Digital Hybrids.

RJ-45 Modular Pinout:

<u>Pin</u>	<u>Description</u>
1)	Ground
2)	Call / Drop Control
3)	Ring / OH LED
4)	DTMF Output
5)	+5 VDC
6)	reserved
7)	reserved
8)	reserved

Maximum cable length, 50 feet.
Size: 3.75" x 4.75" x 1.6" (9.6 x 12 x 4 cm)