



FEATURES

	IL	OL	3.5
» HD Voice (Wide-Band Speech)	•	•	•
» Connects to Headsets, Phones, & Notebooks with Bluetooth Wireless Technology	•	•	
» Connects to Phones and Notebooks with 4-conductor 3.5mm Headset Interface			•
» 2.4 GHz Encrypted Digital Wireless	•		
» 3-pin XLR Male and Female Intercom Jacks	•		
» Uses Standard 4-Pin and 5-Pin Male or Female Intercom Headset Jacks		•	•
» Send and Receive Volume Controls	•	•	•
» Push-On, Push-Off Talk Button	•	•	•
» Recessed Sidetone Level control	•	•	•
» Intercom Powered with 9 Volt Battery Backup	•		
» Number of Hours on one 9 Volt Battery	N/A	10 Hrs	>20 Hrs

In the Loop, Out of Bounds.

Outerloop™ functions as a wireless link to your intercom system. This universal belt pack provides connections for your existing 4-pin or 5-pin intercom headset, routing audio through your mobile device over a Bluetooth wireless connection. Use your mobile device to call into your intercom phone bridge, station phone coupler, or any phone-based intercom app such as Unity Intercom or Clear-Com® Agent-IC.

Universality. Adapting to the mixed-up intercom world, model OTL-F features both 4-pin and 5-pin Female XLR headset jacks, while model OTL-M features both 4-pin and 5-pin Male XLR headset jacks. Easy-to-use send and receive level controls, a push-on, push-off Talk button, as well as a recessed sidetone level control. All the comforts of a standard belt pack whether you are around the corner or around the world.

Outerloop also features a switch that selects between pairing to a phone or to a headset. In Phone mode, Outerloop pairs to your cell phone, notepad, or computer just like any other Bluetooth headset. In Headset mode, you can pair to another Outerloop or to a standard Bluetooth headset, providing a short range secure wireless point-to-point intercom.

HD Voice. Outerloop to Outerloop connections default to HD Voice (120 Hz to 7 kHz) bandwidth. Many new Bluetooth wireless cell phones and headsets also provide HD Voice bandwidth.

Read the HD Voice primer on www.jkaudio.com

Interloop and Outerloop shown for comparison

IL = Interloop **OL** = Outerloop **3.5** = Outerloop 3.5



Outerloop™

Universal Intercom Belt Pack

7 kHz
HD VOICE



REAR VIEW OUTERLOOP-F



OUTERLOOP-M



SPECIFICATIONS

Model Outerloop-F	
Headset:	4-pin Female XLR, 5-pin Female XLR
Model Outerloop-M	
Headset:	4-pin Male XLR, 5-pin Male XLR
Headset Microphone	
Impedance:	50-2000 ohms
Headset Earpiece	
Load Impedance:	50-600 ohms
Power:	>50 mW into 150 ohms

Bluetooth Wireless Technology

Standard:	Bluetooth 3.0
Profile:	Hands Free (HF)
Range:	66 feet (20 Meters)
Frequency Response:	Hands-Free (Full Duplex): 300 Hz– 3.4 kHz Hands-Free (Full Duplex HD): 50 Hz– 7 kHz
Power:	9 VDC Battery
Size:	4.7" x 3.75" x 1.65" (12 x 9.5 x 4.2 cm)
Weight:	10 ounces (275 grams)



The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by JK Audio, Inc. is under license.

